

GO GREEN, SAVE GREEN.



New N-0842MC Series Condensing Tankless Technology

Noritz's newest condensing series not only boasts 94% efficiency but is priced so that you can go green to save the environment while saving some green in your pocket as well.

Built-in PVC Adapter

- Easy and affordable installation
- Zero clearance to combustible venting

Stainless Steel Heat Exchanger

- Residual heat used to pre-heat incoming water
- Durable & corrosion resistant

Copper Heat Exchanger

- Commercial grade copper
- 25% Thicker piping
- Innovative efficient heat distribution design

Built-in Neutralizer

- Added convenience

Temperature Settings From 100°F- 180°F





N-0842MC
 indoor/outdoor use
 3" or 4" PVC only



N-0842MC-DV
 indoor use
 3" or 4" PVC only

		N-0842MC Specifications	
Gas	NG	Max. 199,900 btuh- Min. 11,000 btuh	
Consumption	LP	Max. 199,900 btuh- Min. 11,000 btuh	
Thermal Efficiency	93%		
Energy Factor	NG: 0.91 LP: 0.93		
Hot Water Capacity	35°F Rise	10.6 Gal./min.	
	45°F Rise	8.4 Gal./min.	
	77°F Rise	4.8 Gal./min.	
	100°F Rise	3.7 Gal./min.	
Capacity Range	0.5 - 11.1 Gal./min.		
Temperature Settings	100-150°F (In 5°F intervals), 160, 170, 180°F (14 Options)		
Default Temperature Options	120, 130, 140, 180°F (Default is 120°F)		
Features	Quick-Connect (2 units), Multi-System (Up to 24 units), Pump Control, Temperature Lockout, High Elevation Adjustment		
Warranty	12/5- Residential, 3/5- Commercial or Circulation Use		
Approvals	CSA, UPC, NSF, Low NOx Approved By SCAQMD		
Type	Installation	Indoor/Outdoor, Wall Hung	
	Air Supply/Exhaust	Power Vented, 4" Flue (PVC/CPVC Only)	
Ignition	Direct Ignition		
Operating Water Pressure	15 - 150 PSI		
Minimum Flow Rate	0.5 GPM		
Gas Supply Pressure	NG : 4.0" - 10.5" LP : 8.0" - 14.0"		
Dimensions	24.2"(Height) x 18.3"(Width) x 9.4"(Depth)		
Weight	73 (pounds)		
Water Holding Capacity	0.5 Gallon		
Connection Sizes	Water Inlet	3/4"	
	Hot Water Outlet	3/4"	
	Gas Inlet	3/4"	
	Condensate Drain	1/2"	
Power	Supply	120 VAC (60Hz)	
	Consumption	NG: 106W LP: 109W Freeze Prevention 213W	
Material	Casing	Zincified Steel Plate/Polyester Coating	
	Flue Collar	Stainless Steel	
	Heat Exchangers	Copper Sheeting, Copper Tubing (Primary), Stainless Steel (Secondary)	
Safety Devices	Flame Rod, Thermal Fuse, Lightning Protection Device (ZNR), Overheat Prevention Device, Freezing Prevention Device, Fan Rotation Detector, Neutralizer Overfill Sensor		
Included Accessories	Remote Controller, Remote Controller Cord, Anchoring Screws, Condensate Neutralizer, 4" PVC/CPVC Adapter		
Optional Accessories	Isolation Valves (#IK-WV-4), Outdoor Vent Cap (#VC-4C), Birdscreen (#VT4-PVCS), Remote Controller Outdoor Junction Box (#RC-OJB), ScaleShield (#SS-HB-1), Quick-Connect Cable (#QC-1M), Multi-System Controller (#SC-201-6M, -12M, -24M), Pipe Cover (#PC-3S)		

ACCESSORIES



Remote Controller



Outdoor Junction Box



ScaleShield



Isolation Valves



Pipe Cover

Accessories	Descriptions	Part Number	842MC	842MC-DV
Remote Controller	Remote Controller	RC-7649M	x	x
Remote Controller Cord	10' Length	RC-CORD10	x	x
	26' Length	RC-CORD26	x	x
RC Outdoor Junction Box	RC-OJB	700757	x	
Pipe Covers	Pipe Cover	PC-3S	x	x
Quick-Connect Cable	2-Units Only	QC-1	x	x
System Controller	Up to 6 Units	SC-201-6M	x	x
	Up to 12 Units	SC-201-12M	x	x
	Up to 24 Units	SC-201-24M	x	x
Isolation Valves	Isolation Valves (Includes Pressure Relief Valve)	IK-WV-7-TH	x	x
		IK-WV-7-SW	x	x
ScaleShield	ScaleShield	SS-HB-1	x	x
ScaleShield Refill Cartridges	1 Each	HBC-1	x	x